

EXOfos PB-264

TECHNICAL SPECIFICATION	PRODUCT
NUMBER	STW: EX/1059/1
DATE	2019-04-26
CHEMICAL NAME	POE (4) Lauryl Phosphate
TECHNICAL REQUIREMENTS	<p>Appearance at temperature (20÷25)°C..... viscous liquid</p> <p>Color (Gardner) at (20÷25)°C max 2 (PN-EN ISO 4630-1:2006, visual method)</p> <p>Acid Value (to the first inflection point), mg KOH/g 90 ÷ 110 (MB/ER-033)</p> <p>Acid Value (to the second inflection point), mg KOH/g..... 150 ÷ 180 (MB/ER-033)</p> <p>Free Phosphoric Acid, % (m/m)..... max 2 (MB/ER-033)</p> <p>pH of 10% solution 1.3 ÷ 2.5 (PN-EN 1262:2004, solution B at 20 °C)</p> <p>pH of product..... max 1.2 (PN-EN 1262:2004, at 20 °C)</p> <p>Refractive Index at 20°C 1.458 ÷ 1.462 (PN-EN ISO 6320:2017-04)</p> <p>Kinematic viscosity at 25°C, mm²/s..... 650 ÷ 900 (ASTM D445-15)</p> <p>Water, % (m/m) max 2.0 (PN-ISO 760:2001, direct method)</p>
INFORMATIVE DATA*	-

* These informative data are not technical requirements and cannot form the basis for anyclaims.

USE Product used in metalworking, textile, and hard surface cleaner formulations.

PACKAGING	Packaging with required UN sign. Polyethylene drums with a capacity of 120 liters and other packaging as agreed with the customer.
STORAGE	Store in a tightly closed container in a room protected against atmospheric conditions, at a temperature of up to 40°C. Protect against humidity and high insolation.
SHELF LIFE	Guaranteed period of stability: 12 months from the date of manufacture
TRANSPORTATION	Limitations resulting from ADR, RID, IMDG, ICAO/IATA regulations apply. UN number: 3265 Proper shipping name: Corrosive liquid, acidic, organic, N.O.S. (Contains organic phosphate esters) Transport hazard class(es): 8 Packing group: III Covered means of transport recommended.
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicated herein, please contact PCC EXOL SA for consultation sending an e-mail to: industrial.application@pcc.eu

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice. The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended.